

REFRIGERATED CABINET WITH 1 DOOR



- Stainless steel Exterior/Interior
- Insulation with ecological polyurethane 6 cm
- H.A.C.C.P. rounded corners
- Plastic-coated grills
- Stainless steel pair sheet for Gastronorm Containers
- Height adjustable Inox feet
- Self-closing doors, terminal switch which blocks the ventilator when the door opens
- Ecological Freon
- Air flow system for uniform distribution of cooling



MODEL	US 68
External dimensions (WxDxH) cm.	68 x 80 x 210
Capacity (Lt.)	620
Temperature Range (°C)	-2 to +10
Doors	1
Door Dimensions (WxD) cm.	68 x 163
Plastic-coated grills (Pcs/Dimensions (WxD) cm.)	3 / 53 x 65
Inox Feet (Pcs/Dimensions (H) cm.)	4 / 10 -13
Voltage / Frequency (V/Hz)	220 - 240 / 50
Input Power (W)	450
Compressor (HP)	3/8
Type of Cooling	Fan assisted
Type of Defrost	Automatic
Controller	Digital
Refrigerant	R 134 a
Internal Light	✓
Net Weight (kg)	127
Volume (m3)	1,00

REFRIGERATED CABINET WITH 2 DOORS



- Stainless steel Exterior/Interior
- Insulation with ecological polyurethane 6 cm
- H.A.C.C.P. rounded corners
- Plastic-coated grills
- Stainless steel pair sheet for Gastronorm Containers
- Height adjustable Inox feet
- Self-closing doors, terminal switch which blocks the ventilator when the door opens
- Ecological Freon
- Base for double meat hooks
- Air flow system for uniform distribution of cooling



MODEL	US 135
External dimensions (WxDxH) cm.	135 x 80 x 210
Capacity (Lt.)	1232
Temperature Range (°C)	-2 to +10
Doors	2
Door Dimensions (WxD) cm.	68 x 163
Plastic-coated grills (Pcs/Dimensions (WxD) cm.)	6 / 61 x 61
Inox Feet (Pcs/Dimensions (H) cm.)	4 / 10 -13
Voltage / Frequency (V/Hz)	220 - 240 / 50
Input Power (W)	650
Compressor (HP)	1/2
	Fan assisted
Type of Defrost	Automatic
Controller	Digital
Refrigerant	R 134 a
Internal Light	✓
Net Weight (kg)	185
Volume (m3)	2,27